## **TECHNICAL NOTES**

## U.S. DEPARTMENT OF AGRICULTURE RENO, NEVADA SOIL CONSERVATION SERVICE

JUNE 1993

AGRONOMY TECHNICAL NOTE NO. NV-71

SUBJECT: CPA - ESTIMATING GROSS EROSION FROM FIELD MEASUREMENT OF RILL EROSION IN TONS/ACRE

The attached Idaho Technical Note Agronomy No. 8 is useful in planning areas with slopes that are steep enough to have rill erosion.

Jim W. Doughty State Resource

State Resource Conservationist

# **Technical Notes**

USDA-Soil Conservation Service Boise, Idaho

AGRONOMY TECH NOTE NO. 8 (Rev. 2)

June 1992

Prepared by Floyd G. Bailey, State Conservation Agronomist. The information in this Technical Note was taken from West Technical Service Center's Agronomy Technical Note No. 25, and updated with new technical research data furnished by Dr. D. K. McCool, SEA-AR.

# ESTIMATING GROSS EROSION FROM FIELD MEASUREMENT OF RILL EROSION IN TONS/ACRE

The method explained below for measuring rill erosion is known as the Alutin Rill Erosion Method. This procedure can be used to measure rill erosion up to rates of 100 tons per acre. Losses greater than 100 tons per acre are considered ephemeral gully erosion or concentrated flow erosion and should not be measured using this method.

Tons/acre soil loss from rill erosion = a sum of cross section of rills in square inches along a measured lineal distance of 12.5 feet across the slope or multiples thereof.

- <u>Step 1</u> Measure a lineal distance of 37.5 or 75.0 feet across a slope.
- <u>Step 2</u> Measure in inches, the width and depth of <u>each</u> rill along the chosen distance.
- Step 3 Multiply each width and depth reading to obtain a product in square inches.
- Step 4 Add all products of readings along chosen distance.
- Step 5 Divide this sum by 3 if a 37.5 foot distance was selected, and by 6 if 75.0 feet was chosen. The result is tons of soil loss per acre from rill erosion.

## Example

Station Width (in.) x Depth (in.) = Area in sq. in. along a distance of 37.5 feet

1	3	3	9
2	2	3	6
3	3	6	18
4	4	6	24
5	3	5	15
6	5	6	_30
			102

For the chosen distance of 37.5 feet, the soil loss from rill erosion in tons/acre = 102/3 = 34.

# FIELD MEASUREMENT OF RILL EROSION IN TONS/AC. (Alutin Method)

				Loca			
ield Numbe	r	Pe ar	ercent Slop nd Length _	pe	Soi:	l ies	
ransect R tation W	ill idth	Rill Depth	Square Inches	Transect Station	Rill Width		Square

#### INSTRUCTIONS

The method explained below for measuring rill erosion in tons per acre is known as the Alutin Rill Erosion Method. This procedure measures soil losses up to 100 tons per acre. Losses greater than 100 tons per acre are usually beyond the realm of rilling and are considered to be concentrated flow or ephemeral gully erosion.

The basic formula used in this calculation is:

T/Acre soil loss - summ of cross section of rills in square inches along a measured lineal distance of 13.7 feet across the slope or multiples thereof.

#### Procedure:

- Step 1 Measure a lineal distance of 37.5 or 75.0 feet
  across the slope.
- Step 2 Measure in inches, the width and depth of each rill along the chosen distance.
- Step 3 Multiply each width and depth reading to obtain a product in square inches.
- Step 4 Add all products of readings along chosen distance.
- Step 5 Divide this sum by 3 if a 37.5 foot distance was selected and by 6 if 75.0 feet were chosen. The result if tons of soil per acre.

### Example:

Width (in.)	Depth (in.)	) = Area	in square inches
3	3		9
2	3		6
3	6		18
4	6		24
3	5		15
5	6		30
	To	otal 1	.02

#### Answer:

For a chosen distance of 37.5 feet, the soil loss in tons/ acre - 102/3 = 34 tons.

# FIELD MEASUREMENT OF RILL EROSION IN TONS/AC. (Alutin Method)

				Loca			
Field Num	nber	a	nd Length	oe .	_ Seri	ies	
Transect Station		Rill Depth	Square Inches	Transect Station	Rill Width		Square Inches
							3
*!							